

Application No. 09/557,696

product composition, the second quantity of product composition being materially different from the first quantity of product composition; and collecting the second quantity of product composition from the fluid stream using a second collector.

- SEP 27
- 16
2. The method of claim 1 wherein the composition of the second quantity of fluid reactants is different from the composition of the first quantity of fluid reactants.
  3. The method of claim 1 wherein a reaction condition during the reaction of the second quantity of fluid reactants is different from the reaction condition during the reaction of the first quantity of fluid reactants.
  4. The method of claim 3 wherein the reaction condition is selected from the group consisting of pressure, reactant flux, reactant temperature, amount of inert diluent, amount of radiation absorbing gas, and energy input.
  5. The method of claim 1 wherein the nozzle comprises a plurality of reactant inlets.
  6. The method of claim 1 wherein the nozzle remains fixed and the collectors are moved relative to the nozzle.
  7. The method of claim 1 wherein the collectors remain fixed and the nozzle is moved relative to the collectors.
  8. The method of claim 1 wherein the apparatus has a radiation path defined by a radiation source and directing optical elements and wherein the reacting of the fluid reactants involves interacting radiation from the radiation source with the reactants.
  9. The method of claim 8 wherein the radiation source is an infrared laser.

Application No. 09/557,696

10. The method of claim 1 wherein the reactions are performed in a reaction chamber sealed from the ambient environment.

11. The method of claim 10 wherein the compositions comprise particles and the apparatus further comprises a pump and valves, and wherein the valves are opened and closed such that the first collector is exposed to the forces of the pump while the first quantity of particles are being collected and the second collector is exposed to the forces of the pump while the second quantity of particles are being collected.

12. The method of claim 1 further comprising evaluating the properties of the first quantity of product composition and the second quantity of product composition.

13. The method of claim 1 wherein one of the quantity of reactants is introduced into a reaction zone through a plurality of inlets oriented such that the reactants combine after they pass through the inlets, the reaction of the one quantity of reactants taking place within the reaction zone.

14. The method of claim 1 further comprising delivering the first quantity of reactants through a first nozzle and delivering the second quantity of reactants through a second nozzle.

38. (Amended) A method for producing a mixture of compositions, the method comprising:

reacting a first quantity of fluid reactants to form a first quantity of product composition;

collecting the first quantity of product composition using a collector;

following completion of the collection of the first quantity of product composition,

reacting a second quantity of fluid reactants to form a second quantity of product composition, the second quantity of product composition being materially different from the first quantity of product composition; and

collecting the second quantity of product composition using the collector.

Application No. 09/557,696

39. The method of claim 1 wherein the first quantity of product composition and the second quantity of product composition comprise solid particles.
40. The method of claim 1 wherein the first quantity of product composition and the second quantity of product composition comprises a metal.
41. The method of claim 1 wherein the first quantity of product composition and the second quantity of product composition comprises chemical powders selected from the group consisting of metal/metalloid oxides, metal/metalloid carbides, metal/metalloid nitrides, and metal/metalloid sulfides.
42. The method of claim 1 wherein the first quantity of fluid reactants and the second quantity of fluid reactants comprise vapor reactants.
43. The method of claim 1 wherein the first quantity of fluid reactants and the second quantity of fluid reactants comprise aerosol reactants.
44. The method of claim 1 wherein first quantity of fluid reactants and the second quantity of fluid reactants comprise a metal/metalloid compound.
45. (Amended) The method of claim 12 wherein the step of evaluating the properties comprises evaluating the crystal structure by x-ray diffraction.
46. (Amended) The method of claim 12 wherein the step of evaluating the properties comprises evaluating particle size using dynamic light scattering.
47. (Amended) The method of claim 12 wherein the step of evaluating the properties comprises evaluation of the optical properties.

Application No. 09/557,696

48. The method of claim 47 wherein the optical properties are selected from the group consisting of emission, absorption, Raman scattering, fluorescence and combinations thereof.

49. (Amended) The method of claim 12 wherein the step of evaluating the properties comprises measurement of the electroactive properties.

50. (Amended) The method of claim 12 wherein the step of evaluating the properties comprises measurement of the electrical properties or magnetic properties.

51. (Amended) The method of claim 12 wherein the step of evaluating the properties is performed without removing the products from the collectors.

52. (Amended) The method of claim 12 wherein the step of evaluating the properties is performed after removing the products from the collectors.

53. The method of claim 38 wherein the composition of the second quantity of fluid reactants is different from the composition of the first quantity of fluid reactants.

54. The method of claim 38 wherein the reacting the first quantity of fluid reactants is within a fluid stream and wherein the reacting the second quantity of fluid reactant is within a fluid stream.

55. The method of claim 38 wherein the apparatus has a radiation path defined by a radiation source and directing optical elements and wherein the reacting of the fluid reactant involves interacting radiation from the radiation source with the reactants.

56. The method of claim 38 wherein the reactions are performed in a reaction chamber sealed from the ambient environment.

Application No. 09/557,696

57. The method of claim 38 further comprising evaluating the properties of the mixture.

58. (Amended) A method for obtaining a plurality of quantities of compositions with an apparatus comprising a plurality of collectors and a reactant delivery system comprising a first quantity of fluid reactants and a second quantity of fluid reactants being different from the first quantity of fluid reactants, the method comprising:

reacting the first quantity of fluid reactants within a fluid stream to form a first quantity of product composition;

collecting the first quantity of product composition from the fluid stream using a first collector;

following completion of the collection of the first quantity of product composition, reacting the second quantity of fluid reactants within the fluid stream to form a second quantity of product composition, the second quantity of product composition being materially different from the first quantity of product composition, wherein the second quantity of fluid reactant is different from the first quantity of fluid reactants; and

collecting the second quantity of product composition from the fluid stream using a second collector.

59. The method of claim 58 wherein the first quantity of fluid reactants comprises a different proportion of compounds relative to the second quantity of fluid reactants.

60. The method of claim 58 wherein the first quantity of fluid reactants comprises different compounds than the second quantity of fluid reactants.

61. (Amended) The method of claim 58 wherein the apparatus comprises a nozzle comprising a reactant inlet that moves relative to the plurality of collectors and wherein the nozzle is moved relative to the first collector and second collector following completion of the collection of the first quantity of product composition, at least a portion of the first quantity of fluid reactants

Application No. 09/557,696

being from the reactant inlet and at least a portion of the second quantity of second fluid reactants being from the reactant inlet.

62. The method of claim 58 wherein the apparatus has a radiation path defined by a radiation source and directing optical elements and wherein the reacting of the fluid reactants involves interacting radiation from the radiation source with the reactants.

63. The method of claim 58 further comprising evaluating the properties of the first quantity of product composition and the second quantity of product composition.

64. (Amended) A method for obtaining a plurality of quantities of compositions with an apparatus comprising a plurality of collectors and a reaction chamber isolated from the ambient environment, the method comprising:

reacting in the reaction chamber a first quantity of fluid reactants within a fluid stream to form a first quantity of product composition;

collecting the first quantity of product composition from the fluid stream using a first collector;

following completion of the collection of the first quantity of product composition, reacting in the reaction chamber a second quantity of fluid reactants within the fluid stream to form a second quantity of product composition, the second quantity of product composition being materially different from the first quantity of product composition, wherein at least one reaction condition during the formation of the second quantity of product compositions is different from the reaction condition during the formation of the first quantity of product compositions and wherein the reaction chamber remains isolated from the ambient environment continuously from the reacting of the first quantity of reactants and through the reacting of the second quantity of reactants; and

collecting the second quantity of product composition from the fluid stream using a second collector.

Application No. 09/557,696

65. The method of claim 64 wherein the at least one reaction condition is selected from the group consisting of pressure, reactant flux, reactant temperature, amount of inert diluent, amount of radiation absorbing gas, and energy input.

66. (Amended) The method of claim 64 wherein the apparatus comprises a nozzle comprising a reactant inlet that moves relative to the plurality of collectors and wherein the nozzle is moved relative to the first collector and second collector following completion of the collection of the first quantity of product composition, at least a portion of the first quantity of fluid reactants being from the reactant inlet and at least a portion of the second quantity of second fluid reactants being from the reactant inlet.

67. The method of claim 64 wherein the apparatus has a radiation path defined by a radiation source and directing optical elements and wherein the reacting of the fluid reactants involves interacting radiation from the radiation source with the reactants.

68. The method of claim 64 further comprising evaluating the properties of the first quantity of product composition and the second quantity of product composition.

#### REMARKS

Claims 1-14 and 38-68 are pending. The specification has been updated to add patent numbers for copending applications that have subsequently issued. By this Amendment, claims 1, 38, 45-47, 49-52, 58, 61, 64, and 66 are amended. Claim 38 has been amended to correct a typographical error, and claims 45-47 and 49-52 have been amended for clarity. Claims 1, 61, 64 and 66 have been amended to insert explicitly into the claim a previously implicit feature for clarity. The amendment of claims 1, 61 and 66 is supported by the specification, for example, at page 24, lines 5-11. There is no intention of narrowing the scope of claims 1, 38, 45-47, 49-52, 61, 64 and 66 by the amendments. Claim 58 has been amended to more particularly point out Applicants' invention. The amendment of claim 58 is supported by the specification, for example, at page 10, lines 3-32 and page 20, lines 26-33. No new matter is introduced by the amendments.